

MV: WAAL CONFIDENCE

General

Class	NKK
Class notation	NS*,BCM,IWS,PSCM
Ship type	DHBC
Year built	JUN 2009
Yard	Shin Kochi Japan
DD due	SEPT 04 2022
SS due	JUNE 04 2024

Flag	Portugal
Registry	Madeira
Reg. nr.	TEMP578M
Call Sign	CQA13
IMO nr.	9392092
Telex	425501950
Phone	+870 771 362 010
Email	waalconfidence@speedmailplus.com

Speed & Consumption

Laden	abt. 13.0 kts on abt. 23.5 IFO + abt. 0.1 mt LSMGO
Eco (WOG)	abt. 12.0 kts on abt. 21.5 IFO + abt. 0.1 mt LSMGO
Port Idle	abt. 2.0 mt IFO + abt. 0.1 mt LSMGO
Port WWW	abt. 4.5 mt IFO + abt. 0.1 mt LSMGO
Vessel consumes ULSGO when manoeuvring and sailing in narrow waterways and canals. Speed / Cons. upto windforce BF 4, max. wave height 1.25 m, max. swell height 2.00 m, no adverse current, no influence of swell and even-keel condition. Bunker specs: IFO ISO 8217:2017 (E) RMG 380 / ULSGO: ISO 8217:2017 (E) DMA (max 0.1% Sulphur) Sulphur specs and each delivery and burning of specific types (grades) of bunkers always to comply with MARPOL regulations a/o EU directives a/o USA a/o any other national regulations including latest amendments	

Principal dimensions

Length over all	179.99	m
Breadth moulded	28.20	m
Depth moulded	14.30	m
Summer draft	10.031	m
Summer dwt	33,387	MT
TPC (summer)	44.55	t/cm
GT/NT	21192/11444	T
Lightweight	7283	T
Suez Gross/Nett	21335/19474	T
Panama PC/UMS	17674	T

W/L-H/c Summer	6.39	m
W/L-H/c Ballast mid.	10.90	m
Keel – Top H/c	16.42	m
Keel – Top of mast	42.84	m
VLSFO cap. (85%)	1073	m ³
ULSGO cap. (85%)	295	m ³
FW capacity (100%)	310	m ³
Ballast cap. (100%)	12579	m ³
Slop tanks (CH wash)	167	m ³

Operational restrictions

No mixing of new bunkers with bunkers already onboard.
Vessel is only allowed to work single hook on a single hatch
Constants could be affected due to vessel retaining onboard of hold cleaning water and/or grey water as per MARPOL regulations.

Bunker tank capacities could be affected due to vessel having to keep different IFO and ULSGO grades separated as a consequence of compliance with Marpol regulations a/o EU directives a/o USA a/o any other national regulations including latest amendments.

This vessel is member of an independent fuel testing system (Intertek Lintec). Charterers or their representatives are always at liberty to witness the sampling during any bunkering of the vessel under the charter and any discrepancies found between supplier's sample and Intertek Lintec sample then the Intertek Lintec sample to be final and binding. As long as the analysis results of the fuel oil onboard has not been received and approved by Owners, the vessel may have to use ULSGO instead

Cargospaces

Cap. (ft³)	Grain	Bale
C/H #1	247042	244509
C/H #2	340265	333710
C/H #3	341148	333872
C/H #4	341148	333872
C/H #5	306925	299595
Total	1576528	1545558

Floor space	LxB/H/Ba/H(m)	Hatch Size
C/H #1	26.00x7.00/23.60	16.80x17.20
C/H #2	28.40x23.60	20.80x23.80
C/H #3	28.40x23.60	20.80x23.80
C/H #4	28.40x23.60	20.80x23.80
C/H #5	27.60x7.0/23.60	19.20x23.80

drft(m)	Deadweight
10.03	Summer 33387
10.23	Trop. 34315
10.46	TropF. 34296
10.25	Fresh 33387
9.82	Winter 32461

Ventilation	Elec.
Airchanges	2.2 / h
CO2 fitted	Fitted
A60 bkhd	N/A
Smoke det.	N/A
Aussie fitted	Fitted
Dehumidifier	N/A

*Note: In case of heavy cargoes to be loaded, the maximum quantity is to be in accordance with vessel's loading and stability booklets.

Strength

	CH#1	CH#2	CH#3	CH#4	CH#5		
Hatchcovers	N/A	N/A	N/A	N/A	N/A	t/m ³	*observe load manual
Weatherdeck	N/A	N/A	N/A	N/A	N/A	t/m ³	
Tanktop	20	20	20	20	20	t/m ³	*Local strength
Tanktop	12.50	12.50	12.50	12.50	12.50	t/m ³	*Uniform distributed
Steel Coils	Standard coil loading condition - 2 tiers x 21 T coils (breath 1.8 m) 4 dunnages.						
*Note: Alternate hold loading condition (Nos. 2 & 4 may be empty). No alternate ore loading							
*Note 2: Other coil loading conditions subject to owners approval of local stress calculations.							

Deck equipment

Hatch type	Hydr. End-folding type, DS
Maker	MacGregor-Kayaba, Ltd.
Cargo gear type	Electr/hydr. 30t x 24m x 4 sets
Maker	Mitsubishi Heavy Industries
Outreach	9.90 mtr
Grab handling	TBA
Grabs fitted	N/A
De-ballast Cap.	Max. 600 M ³ / H

Features

ITF fitted	Yes
Log fitted	No
WBTS fitted (AMS approved)	Yes
Lakes fitted	No
Suitable for grab discharge	Yes

Machinery details

Main engine	Mitsubishi 6UEC52LA
NCO	5313 KW @ 112 rpm
Aux. engines	Yanmar 6 N18AL-DV – 2 sets
Electrical	562 KVA / 450V / 60 Hz / 900 rpm
Freshwater generator	Max. 15l/day

All details "about" given in good faith, without guarantee.